

[Podręcznik użytkownika](#) > Konfiguracja OutlookDAV Synchronizer dla Office 2007-2013

Konfiguracja OutlookDAV Synchronizer dla Office 2007-2013

Pomyślnie próbę synchronizacji zdarzeń/spotkań z kalendarza przeszedł program Outlook CalDav Synchronizer oferujący wsparcie dla protokołu CalDAV. Outlook CalDav Synchronizer jest bezpłatnym dodatkiem do Outlooka. Możemy pobrać go z tej [lokalizacji](#).

Po zainstalowaniu dodatku w programie Outlook pojawia się dodatkowy pasek narzędzi.



Dodanie profili dla synchronizacji spotkań oraz zadań dodajemy poprzez kliknięcie w **Synchronization Profiles**.

Dodanie profilu dla spotkań

 A screenshot of the 'Options' dialog box for the OutlookDAV Synchronizer. The dialog is titled 'Options' and has a tree view on the left with two items: 'eDokumenty Spotkania' (selected) and 'eDokumenty TODO'. The main area is divided into several sections:

- Name:** eDokumenty Spotkania
- Outlook Settings:**
 - Outlook folder: Kalendarz
 - ☒ Synchronize items immediately after change
- Server settings:**
 - DAV Url: http://[ADRES_EDOKUMENTOW]/dav.php/calendars/[NAZWA_UZYTKOWNIKA]/work/
 - Username: [NAZWA_UZYTKOWNIKA]
 - Password: [REDACTED]
 - ☐ Use IMAP/POP3 account password
 - Email address: [ADRES_MAILOWY]
 - Test settings button
- Sync settings:**
 - Synchronization Mode: Outlook ↔ Server (Two-Way)
 - Conflict Resolution: Automatic
 - Synchronization interval (minutes): 30
 - ☒ Use time range filter
 - Synchronization timespan past (days): 60
 - Synchronization timespan future (days): 180
 - Buttons: Delete, Copy, Clear cache

 At the bottom left is an 'Add' button, and at the bottom right are 'Ok' and 'Cancel' buttons.

Dodanie profilu dla zadań

The screenshot shows the 'Options' dialog box for 'eDokumenty TODO'. The left sidebar lists 'eDokumenty Spotkania' and 'eDokumenty TODO'. The main area is divided into three sections:

- Outlook Settings:** 'Outlook folder:' is set to 'Zadania'. There is a checkbox for 'Synchronize items immediately after change' which is unchecked.
- Server settings:** 'DAV Url:' is 'http://[ADRES_EDOKUMENTOW]/dav.php/calendars/[NAZWA_UZYTKOWNIKA]/work/'. 'Username:' is '[NAZWA_UZYTKOWNIKA]' and 'Password:' is masked with '*****'. There is a checkbox for 'Use IMAP/POP3 account password' which is unchecked. 'Email address:' is empty. A 'Test settings' button is at the bottom right of this section.
- Sync settings:** 'Synchronization Mode:' is 'Outlook ↔ Server (Two-Way)'. 'Conflict Resolution:' is 'Automatic'. 'Synchronization interval (minutes):' is '30'. There is a checked checkbox for 'Use time range filter'. 'Synchronization timespan past (days):' is '60' and 'Synchronization timespan future (days):' is '180'. At the bottom right of this section is a checked checkbox for 'Is active'.

Buttons at the bottom include 'Add', 'Delete', 'Copy', 'Clear cache', 'Ok', and 'Cancel'.

W przypadku, gdy pracujemy w systemie, gdzie występuje wiele jednostek, w konfiguracji DAV Url wpisujemy:

```
http://[ADRES_EDOKUMENTOW]/dav.php/calendars/[NAZWA_UZYTKOWNIKA]/work_[SYMBOL_JEDNOSTKI]/
```

Znane problemy

Podczas konfiguracji możemy napotkać następujące problemy:

1. Brak poprawności połączenia gdy korzystamy z <https://> w takim przypadku należy sprawdzić adres przez <http://>
1. Brak uprawnień z dostępem do pliku dav.php. W tym celu w konfiguracji Apache2 - `/etc/apache2/mods-available` wprowadzamy modyfikacje w pliku **userdir.conf**

Domyślny plik w systemie Linux Debian

```
<IfModule mod_userdir.c>
    UserDir public_html
    UserDir disabled root

    <Directory /home/*/public_html>
        AllowOverride FileInfo AuthConfig Limit Indexes
        Options MultiViews Indexes SymLinksIfOwnerMatch IncludesNoExec
        <Limit GET POST OPTIONS>
            Order allow,deny
            Allow from all
        </Limit>
        <LimitExcept GET POST OPTIONS>
```

```

                Order deny,allow
                Deny from all
            </LimitExcept>
        </Directory>
</IfModule>

```

Plik userdir.conf po modyfikacjach

```

<IfModule mod_userdir.c>
    UserDir public_html
    UserDir disabled root

    <Directory /home/*/public_html>
        AllowOverride FileInfo AuthConfig Limit Indexes
        Options MultiViews Indexes SymLinksIfOwnerMatch IncludesNoExec
        <Limit GET POST OPTIONS ''HEAD REPORT''>
            Order allow,deny
            Allow from all
        </Limit>
        <LimitExcept GET POST OPTIONS ''HEAD REPORT''>
            Order deny,allow
            Deny from all
        </LimitExcept>
    </Directory>
</IfModule>

```

Po wprowadzeniu modyfikacji w pliku userdir.conf wykonujemy restart Apache

```
/etc/init.d/apache2 restart
```