

Wikiprint Book

Title: TracLinks in reStructuredText

Subject: eDokumenty - elektroniczny system obiegu dokumentów, workflow i CRM - WikiRestructuredTextLinks

Version: 1

Date: 08/24/24 19:13:21

Table of Contents

TracLinks in reStructuredText

3

TracLinks in reStructuredText

This document illustrates how to use the `..trac::` directive in reStructuredText. The page is written like

```

{{{
#!rst

Examples:
* Tickets: :trac:`#1` or :trac:`ticket:1`
* Ticket comments: :trac:`comment:ticket:1:2`
* Reports: :trac:`{1}` or :trac:`report:1`
* Changesets: :trac:`r1`, :trac:`[1]` or :trac:`changeset:1`
* Revision log: :trac:`r1:3`, :trac:`[1:3]` or :trac:`log:@1:3`, :trac:`log:trunk@1:3`
* Diffs (since version 0.10): :trac:`diff:@20:30`, :trac:`diff:tags/trac-0.9.2/wiki-default//tags/trac-0.9.3/wiki-default`
* Wiki pages: :trac:`CamelCase` or :trac:`wiki:CamelCase`
* Milestones: :trac:`milestone:1.0`
* Attachment: :trac:`attachment:ticket:944:attachment.1073.diff`
* Files: :trac:`source:trunk/COPYING`
* A specific file revision: :trac:`source:/trunk/COPYING@200`
* A particular line of a specific file revision: :trac:`source:/trunk/COPYING@200#L25`

}}}
```

Provided you have docutils installed, the above block will render as:

Examples:

- Tickets: [#1](#) or [ticket:1](#)
- Ticket comments: [comment:ticket:1:2](#)
- Reports: [{1}](#) or [report:1](#)
- Changesets: [r1](#), [\[1\]](#) or [changeset:1](#)
- Revision log: [r1:3](#), [\[1:3\]](#) or [log:@1:3](#), [log:trunk@1:3](#)
- Diffs (since version 0.10): [diff:@20:30](#), [diff:tags/trac-0.9.2/wiki-default//tags/trac-0.9.3/wiki-default](#) or [diff:trunk/trac@3538//sandbox/vc-refactoring/trac@3539](#)
- Wiki pages: [CamelCase](#) or [wiki:CamelCase](#)
- Milestones: [milestone:1.0](#)
- Attachment: [attachment:ticket:944:attachment.1073.diff](#)
- Files: [source:trunk/COPYING](#)
- A specific file revision: [source:/trunk/COPYING@200](#)
- A particular line of a specific file revision: [source:/trunk/COPYING@200#L25](#)

Note also that any of the above could have been written using the alternate syntax for roles:

```

{{{
#!rst

See _`ticket:123`

.. trac:: ticket:123 Ticket 123
}}}
```

See [ticket:123](#)

[Ticket 123](#)

The above form has the additional benefit of allowing you to specify an explicit label for the link.

See also: [WikiRestructuredText](#), [TracLinks](#)